

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number  
**WO 2005/062189 A1**

(51) International Patent Classification<sup>7</sup>: **G06F 13/40**

(21) International Application Number:  
PCT/NL2003/000933

(22) International Filing Date:  
24 December 2003 (24.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON** (publ)  
[SE/SE]; SE-164 83 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HAGEMAN, Halbe**  
[NL/NL]; Abdusstraat 83, NL-4841 HG Prinsenbeek (NL).

(74) Agents: **VAN WESTENBRUGGE, Andries et al.**; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MULTISECTIONAL BUS IN RADIO BASE STATION AND METHOD OF USING SUCH A RADIO BASE STATION



(57) Abstract: A communication system has a monitor (31), memory (33,49) and one or more resources (35(i), 37(j), 39(k), 41(m), 43(n), 45(o), 47(p)). The memory (33,49) is connected to the monitor (31) and stores tasks and data. Each of the resources (35(i), 37(j), 39(k), 41(m), 43(n), 45(o), 47(p)) is connected to the monitor (31) and performs a function or executes a program. The bus (51) is implemented by a plurality of adjacent sections, each section being implemented as an ASIC connected to a resource.

WO 2005/062189 A1